





DS06M Series SIP IP Video Intercom



- It's not only a intercom with access control and two way talk but also an IP camera with motion alarm and recording.
- The intercom units come with a 3- Channel controller allows you to connect up to 3 executive units to the intercom, like e- locks, lights, and RFID reader...
- Compatible with all devices and systems that supports SIP – sip ip phone and PBX etc.
- Free professional software for management and Android/IOS mobile apps.
- Facial access allows automatic access without any additional equipment.
- It does not depend on any server; the IP video intercom system can be used in an existing LAN, even no Internet, support DDNS and UPNP for WAN use.
- High quality - 3 years warranty, we protect our customer by offering high quality and reliable products.

## Features

- 1,3 MP, 1/3" SONY Exmor, 2.8mm Pinhole lens.
- IR-Illumination (up to 10 m.), DWDR, 2D/3DNR,
- Built-in Speaker and Microphone,
- Real-Time Remote Access ,
- Vandal-resistant Housing, IK10
- Power through PoE or 12 V (DC), -40°C ~ +50°C
- Pre-installed micro SDHC memory card (8 GB)



**PoE**



**Modbus**

**SIP**



- Field of view adjustment: rotatable body.
- Vandal resistant: metal body ,hidden fixed lens
- Wide range of electric locks support
- Back light compensation, noise reduction
- Real time video in all resolutions
- Exceptional light sensitivity, day/night.
- Wide range of network protocols support

Model:DS06MP 1ch Rely

## General

<b>Image sensor</b>	1,3 MP, Color, 1/3" SONY Exmor, Day/Night
<b>Sensitivity</b>	0.01 lux (Day) / 0.003 lux (Night) / 0 lux (IR Illumination)
<b>Lens</b>	2.8 mm, F2.0
<b>Field of view</b>	80° (horizontal), 53° (vertical),
<b>Field of view adjustment</b>	-45 ~ 45°
<b>Minimum working distance</b>	0.2m
<b>Zoom</b>	Digital, via the web-interface
<b>WDR</b>	Digital, 3 precets
<b>Noise reduction</b>	2D/3DNR (level adjustment), Smart NR
<b>Shutter time</b>	1/25 ~ 1/8000 s (Auto, maximum value setting)
<b>Signal/Noise ratio</b>	50 dB or greater
<b>Synchronization</b>	Light source synchronization 50, 60 Hz
<b>Ringtone patterns</b>	Set by the user
<b>Other features</b>	Electric Mechanical IR filter, Progressive Scanning

## Video

<b>Compression</b>	H.264 BP/MP, Motion JPEG
<b>Video streaming</b>	Dual codec:: H.264/MJPEG, H.264/H.264, MJPEG/MJPEG
<b>Resolution</b>	Main stream: 1280x960 (SXGA), 1280x720 (HD) Sub stream: 720x576, 640x480, 320x240
<b>Frame rate</b>	Up to 25 fps in all resolutions
<b>Bit rate</b>	32 kbps ~ 16 Mbps
<b>Image settings</b>	Brightness, contrast, sharpness, saturation, exposure, color grading, hue, quality, rotation, flip (vertical/horizontal), ART, white balance, exposure time (set gain and minimum value)
<b>Subtitles</b>	Title, date/time, weekday, bit rate, Frame rate, number of connections

## Audio

<b>Audio output</b>	Built-in speaker
<b>Audio input</b>	Built-in microphone
<b>Compression</b>	G.711 (a-law, u-law), G.726
<b>Other features</b>	Duplex

## Illumination

<b>IR illumination</b>	IR LED (3rd generation, 1 pcs)
<b>Control</b>	Auto ON/OFF
<b>Operating mode</b>	By IR sensor, by video viewing, continuous
<b>Wavelength</b>	850 nm
<b>IR distance</b>	Up to 10 m

## Network & Interfaces

<b>Network interface</b>	10Base-T/100Base-TX
<b>Protocols</b>	TCP/IP, SIP v.2.0, VPN, HTTP, HTTPS, FTP, SMTP, DDNS, DHCP, PPPoE, RTP, RTSP, UDP, NTP, ONVIF v.2.41, Modbus TCP, Camdrive
<b>Alarm output</b>	1 channel (NO mode)
<b>Connection</b>	DHCP, static IP address
<b>Users</b>	Up to 3 accounts

### Recording & events

<b>Events</b>	Motion detection, network failure, call button pressing
<b>Motion detection</b>	Build-in video motion detector, up to 4 detection zones (sensitivity adjustment)
<b>E-mail notification</b>	At events: Images
<b>FTP, memory card</b>	At events: Images, video

### Operation

<b>Power</b>	12 V 0.5 A (DC)
<b>Power consumption</b>	Max. 5 W
<b>Commutation current</b>	Up to 1 A
<b>Operating temperature</b>	-40°C ~ +50°C
<b>Ingress protection</b>	IP54
<b>Housing</b>	Vandal resistant
<b>Hosing material</b>	Metal
<b>Dimensions</b>	73x166x51 mm
<b>Weight</b>	570 g
<b>Color</b>	Dim black / Metallic grey
<b>Control</b>	Beward Intercom professional software (included)
<b>System requirements</b>	Microsoft Internet Explorer 9.0 Windows 8/7/Vista, IOS 6.0-9, Android 4.0 later

### Package contents

<b>Units</b>	Door station with installed memory card
	Bracket (2 parts)
	Secret screw
	RJ-45 connectors (2pcs)
	Junction box
	Fixing set
	Clip connector
	CD with manuals and software
	Package

## Dimensions

